

technical specifications

VK-IPC-T141-L



4 MP
2.8 mm



smart dual light
IR and white light



SMD
human detection



IP67
metal & plastic case

Camera

Image sensor	1/2.8" CMOS
Max. resolution	4MP, 2560 (H) x 1440 (V)
Electronic shutter	Auto 1/25 s - 1/1000 s
Min. illumination	0.01 Lux
S/N Ratio	> 56 dB
Illumination distance	IR light 30 m / white light 20 m
Illuminator control	Auto/Manual

Lens

Lens type	Fixed-focal
Focal length	2.8 mm
Max. aperture	F/2.0
Iris type	Auto

Video

Compression	H.264H/H.264M/H.264B/H.265
Video frame rate	Main Stream: 4MP (1 fps-25/30 fps) Sub Stream: D1 (1 fps-25/30 fps)
Bit rate control	CBR/VBR
Video bit rate	H.264: 1792 Kbps-4 Mbps H.265: 1792 Kbps-4 Mbps
Day/Night	Color/B/W
BLC	Yes
HLC	Yes
AWB	Yes
AGC	Auto/Manual
WDR	DWDR
Motion detection	OFF/ON (4 areas, rectangular)
Noise reduction	3D NR
Image rotation	0°/180°
Mirror	Yes
Privacy masking	4 areas

Intelligence

Smart motion detection	Yes
Human detection	Support

Alarm

Alarm event	network disconnection; IP conflict
-------------	------------------------------------

Network

Network	RJ-45 (10/100 Base-T)
SDK and API	Yes
Network protocol	TCP/IP, UDP, HTTP, DHCP, DDNS, FTP, UPNP
Interoperability	ONVIF, CGI
Browser	IE8 and later

General

Power supply	12V DC (±30%) / PoE (802.3af)
Power consumption	Max.: 3W
Operating conditions	-30°C to +60°C / Less than 95% RH
Storage conditions	-40°C to +60°C
Protection grade	IP67
Casing	cover ring: plastic / case: metal
Dimensions	∅ 110 mm x 97 mm

Available models:
VK-IPC-T141-L
VK-IPC-T141-L-B